

# W485N (9.0 kg)



W485N (9.0 kg)

**Solid mount construction with robust frame in galvanized steel**

**Low water consumption up to 12 litre/kg dry linen (60°C without pre-wash). Depending on application.**

**Compass Control® microprocessor offers:**

- Large display and one dial for easy program selection
- Live demonstration (flash application)
- Language selection
- Two Quick Start buttons for frequently used wash programs
- Wash program packages optimized on Economy, Performance and Time

**Four compartment soap box for manual dosing of powder or liquid detergent**

**Large door opening for easy loading/unloading.**

**Stainless and galvanized steel in all vital parts for high degree of rust protection**

**Options**

Drum volume in liters:	85
Max. capacity Kg/lbs:	9/20
Extraction rpm/G-factor:	587/100
Electric heating, kW:	7.2
Non-heated:	Option
Direct steam heating:	Option
Water consumption (liters cold and hot per load):	55/15
Electricity consumption kWh per load:	0.5

Automatic liquid detergent supply (optional I/O board  
for Compass Control)  
Stainless steel front panel  
Stainless steel side panels (only for Milk farm  
version)  
Connection of coin meter  
Drain pump

**Electrolux Laundry Systems, 99 Oakley Road, Luton, Beds, LU4 9GE Tel: 08444 631 260**