

Commercial Laundry Equipment



www.laundrymachines.co.uk FREEPHONE: 08000 288 525

SPECIFICATIONS

Details	Units	HW72	HW94	HW131	HW164
Capacity	Kg (lb)	7.5 (16)	10 (22)	13.5 (30)	16.5 (35)
Height	mm	1005	1005	1170	1170
Width	mm	660	660	780	780
Depth	mm	788	888	900	900
Net Weight	Kg	203	208	287	347
Drum Volume	m ³	0.072	0.094	0.131	0.164
G.Force	Nm	296	296	363	363
Door Opening Dia	mm	300	300	300	300
Control		MICRO 20	MICRO 20	MICRO 20	MICRO 20
Fixing Down		Soft Mount	Soft Mount	Soft Mount	Soft Mount
Electrics- 9kw Heater	Volt/ph/Amp	240/1/45	240/1/45	240/1/45	240/1/45
Electrics- 6kw Heater	Volt/ph/Amp	240/1/32	240/1/32	240/1/32	240/1/32
Electrics- Steam Heated	Volt/ph/Amp	240/1/13	240/1/13	240/1/13	240/1/13
Electrics- 12kw Heater	Volt/ph/Amp	n/a	415/3/32	415/3/32	415/3/32
Electrics- 9kw Heater	Volt/ph/Amp	415/3/20	415/3/20	415/3/20	415/3/20
No.of Water Connections	cold/hot	2/1	2/1	2/1	2/1
Size	" BSP	3/4	3/4	3/4	3/4
Drain Connection (Gravity)	mm	50	50	50	50
Steam Rating	Kg(lb)/cycle	7.2 (15.8)	9.5 (21)	13.2 (29)	16.5 (36)
Size	"BSP	3/8	3/8	3/8	3/8

IPSO HW 'A' SERIES

IPSO HW72A, 94A, 131A, 164A High Speed Spin, Soft Mount Washer

Machines in the HW 'A' range are ideal for the highest contamination risk sites such as hospitals, care homes, veterinary surgeries and stables. They meet NHS Guidelines HSG 95(18) and Category 5 of the latest Water Regulations and comply with the National Minimum Care Standards.

Features

- Built-in Type 'A' air gap
- Microprocessor controlled
- Soft mount
- Two spin speeds
- Information display
- Two sluice programmes
- High build quality with stainless steel cabinet and drums
- Economy button
- Simple to use
- Liquid soap injection control board

Benefits to customer

- Eliminates the risk of water contamination and fully approved for direct connection to mains water, resulting in lower installation costs
- Standard with 9 customised wash cycles to suit individual needs
- Lower installation cost
- 1000rpm super spin, reduces drying time by up to 30% - saves cost, increases throughput and eliminates need for separate hydro extractor. Standard spin speed for delicates prevents creasing and fabric damage
- Displays minutes remaining until the end of cycle enabling more efficient use of staff time
- Displays cycle selected and operating temperature
- Separate programmes for both thermal and chemical disinfection depending on type of fabric being processed. Enables all laundry including heat labile fabrics to be processed without handling
- Clean and hygienic, robust and reliable
- Speeds up the wash cycle for lightly soiled garments
- There are just three stages to starting the 'A' series: choose the appropriate wash programme, select economy button if required and push start
- Easy connection to auto-dosing pump system